
.156--1.451 Ø10.000-KEY SIZE Ø3.626 Ø2.687 BORE DIA. **←** 2.228 **►**

HHCS 1/4-20 [3X] TORQUE TO 108 IN-LBS



ASSY NO.	BORE DIA.	KEY SIZE
4803-0108	.500	1/8 X 1/8
4803-0110	.625	3/16 X 3/16
4803-0112	.750	3/16 X 3/16
4803-0114	.875	3/16 X 3/16
4803-0116	1.000	1/4 X 1/4
4803-0118	1.125	1/4 X 1/4
4803-0120	1.250	1/4 X 1/4
4803-0122	1.375	5/16 X 5/16
4803-0124	1.500	3/8 X 3/8
4803-0126	1.625	3/8 X 3/8

	R/NH/	M® 🦼	A Owned and Operated	
UNLESS OTHERWISE SPECIFIED: DO NOT SCALE DRAWING REMOVE ALL BURRS	THIRD ANGLE PROJE	CTION DESIGNER CR	date 5/25/2022	
TAP DEPTHS FULL THRD DRILL DEPTHS FULL DIA.		REVISED BY	DATE	
TOLERANCES $.XX = \pm .010$ $.XXX = \pm .005$ $.XXXX = \pm .0005$	MATERIAL	10 IN DIS HUB ASSE	SC WITH QD EMBLIES	
THREADS	WEIGHT 5.227 lbr	nass		
EXTERNAL CLASS 2A INTERNAL CLASS 2B		SIZE DRAWING NO.		REV
	1 : 1 1 of 1	D		

- DISC MATERIAL: MILD CARBON STEEL FLAT WITHIN .020", STRESS RELIEVED AND GROUND
- BUSHING/HUBS: QUICK DISCONNECT
- KEYS NOT INCLUDED
- TORQUE BUSHING BOLTS TO 108 IN-LBS
- MAX BRAKE TORQUE RATING: 3,500 IN-LBS